

CLAIMS

WHAT IS CLAIMED:

1. A communications system, comprising:

physical layer hardware adapted to communicate data over a communications channel

5 in accordance with a plurality of control codes, the physical layer hardware being adapted to demodulate an incoming analog signal to generate a digital receive signal and modulate a digital transmit signal to generate an analog transmit signal; and

a processing unit adapted to execute a privileged driver for interfacing with the physical layer hardware, the privileged driver including program instructions for implementing a protocol layer to decode the digital receive signal, encode the digital transmit signal, and configure the physical layer hardware for receipt of the digital receive signal and transmission of the digital transmit signal based on the plurality of control codes.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

2. The system of claim 1, further comprising a memory adapted to store a privileged code, the privileged code, when executed by the processing unit being adapted to define an instruction for configuring the physical layer hardware as a privileged instruction, receiving a request to execute the privileged instruction from a calling program, determine if the calling program has authority to execute the privileged instruction, and execute the privileged instruction in response to determining the calling program has the authority to execute the privileged instruction.

3. The system of claim 2, wherein the privileged code, when executed, is adapted to determine if the calling program comprises the privileged driver.

4. The system of claim 2, further comprising a first and second register, wherein the privileged code, when executed, is adapted to write to the first and second registers to define a memory region in a computer system where the privileged instruction resides.

5

5. The system of claim 2, wherein the privileged code, when executed, is adapted to determine if the calling program has authority to execute the privileged instruction by referencing a stack of a computer system to verify the identity of the calling program.

6. The system of claim 2, wherein the privileged code, when executed, is adapted to determine if the calling program has authority to execute the privileged instruction by authenticating the calling program.

7. The system of claim 2, wherein the privileged code, when executed, is adapted to receiving the request to execute the privileged instruction by receiving an exception generated by the processing unit in response to the calling program attempting to execute the privileged instruction.

8. The system of claim 1, wherein the control codes include at least one of a power level assignment, a frequency assignment, and a time slot assignment.

9. The system of claim 1, wherein the processing unit comprises a microprocessor.

10. The system of claim 1, further comprising:

a processor complex adapted to execute the privileged code;  
a bus coupled to the processor complex; and  
an expansion card coupled to the bus, the expansion card including the physical layer hardware.

5

11. A communications system, comprising:

physical layer hardware adapted to communicate data over a communications channel  
in accordance with a plurality of control codes, the physical layer hardware  
being adapted to demodulate an incoming analog signal to generate a digital  
receive signal and modulate a digital transmit signal to generate an analog  
transmit signal;

a processing unit adapted to execute a privileged driver for interfacing with the  
physical layer hardware, the privileged driver including program instructions  
for implementing a protocol layer to decode the digital receive signal, encode  
the digital transmit signal, and configure the physical layer hardware for  
receipt of the digital receive signal and transmission of the digital transmit  
signal based on the plurality of control codes;

a memory adapted to store a privileged code, the privileged code, when executed by  
the processing unit, being adapted to define an instruction for configuring the  
physical layer hardware as a privileged instruction, receiving a request to  
execute the privileged instruction from a calling program, determine if the  
calling program has authority to execute the privileged instruction, and  
execute the privileged instruction in response to determining the calling  
program has the authority to execute the privileged instruction.

20

25

12. A method for configuring a transceiver, comprising:  
demodulating an incoming analog signal to generate a digital receive signal based on  
a plurality of control codes;  
modulating a digital transmit signal to generate an analog transmit signal based on the  
control codes; and  
executing a privileged driver for configuring the plurality of control codes.

13. The method of claim 12, further comprising:  
defining an instruction for configuring the control codes as a privileged instruction;  
receiving a request to execute the privileged instruction from a calling program;  
determining if the calling program has authority to execute the privileged instruction;  
and  
executing the privileged instruction in response to determining the calling program  
has the authority to execute the privileged instruction.

14. The method of claim 13, wherein determining if the calling program has  
authority to execute the privileged instruction further comprises determining if the calling  
program comprises the privileged driver.

15. The method of claim 13, wherein determining if the calling program has  
authority to execute the privileged instruction further comprises referencing a stack of a  
computer system to verify the identity of the calling program.

16. The method of claim 13, wherein determining if the calling program has authority to execute the privileged instruction further comprises authenticating the calling program.

17. The method of claim 13, wherein receiving the request to execute the privileged instruction further comprises receiving an exception in response to the calling program attempting to execute the privileged instruction.

18. The method of claim 12, wherein demodulating the incoming analog signal based on the plurality of control codes further comprises demodulating the incoming analog signal based on at least one of a frequency assignment, and a time slot assignment.

19. The method of claim 12, wherein modulating the digital transmit signal based on the control codes further comprises modulating the digital transmit signal based on at least one of a power level, a frequency assignment, and a time slot assignment.

20. A method for configuring a transceiver, comprising:

demodulating an incoming analog signal to generate a digital receive signal based on a plurality of control codes;

modulating a digital transmit signal to generate an analog transmit signal based on the control codes;

executing a privileged driver for configuring the plurality of control codes;

defining an instruction for configuring the control codes as a privileged instruction;

receiving a request to execute the privileged instruction from a calling program;

determining if the calling program has authority to execute the privileged instruction;  
and

executing the privileged instruction in response to determining the calling program  
has the authority to execute the privileged instruction.

5

21. A communication system, comprising:

means for demodulating an incoming analog signal to generate a digital receive signal  
based on a plurality of control codes;

means for modulating a digital transmit signal to generate an analog transmit signal  
based on the control codes; and

means for executing a privileged driver for configuring the plurality of control codes.

22. The system of claim 21, further comprising:

means for defining an instruction for configuring the control codes as a privileged  
instruction;

means for receiving a request to execute the privileged instruction from a calling  
program;

means for determining if the calling program has authority to execute the privileged  
instruction; and

means for executing the privileged instruction in response to determining the calling  
program has the authority to execute the privileged instruction.